


DIGITUS® CAT 6, Class E Keystone Module, unshielded





Abstract

DIGITUS® CAT 6, Class E Keystone Module, unshielded, toolfree installation

Features

- Cable entry: Rear side

- Material housing: Abs halogen free, UL 94 VO

- Contacts: Phosphor, bronze

- Coating of contacts: Nickel, gold plated 0.6 μ - Operating temperature: -10 °C bis +50 °C - Material circuit board: FR4, 1.2 mm

- Mating cycles: ≥ 750

- RJ45 outlet for mounting in Patch Panel

IDC contacts: Phosphor, bronze
Layer: 50 μm gold over 40 μm nickel

- Cable connection type: Tool free with cable hatch for strong/flexible conductions AWG 23-26

- Wiring standard: EIA/TIA 568 A/B

- Conformity: Category 6 / 1GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002

- Dimensions: 35x25x17 mm

- Weight: ca. 12 g

- Compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels

- Opening dimensions according to Keystone standard 19.35x14.8 \mbox{mm}

Product Overview

The Item "DN-93603" from DIGITUS® is an unshielded Keystone Module with tool free installation which provides best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels It is conform to Category 6 / 1GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002 and certificated by GHMT.

Product Number Information

DN-93603 DIGITUS® CAT 6 Keystone Module, unshielded, RJ45 to LSA, toolfree installation,

incl. cable tie



Product Images





Technical Drawings

