

LM55-S400

55" UHD LED Monitor



Technical Specification

Model

Model	LM55-S400
-------	-----------

Specification

Diagonal	55"(16:9)
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/m ²
Contrast	5500:1
Display Color	10bit(1.07B)
Viewing Angle	178°/178°(vertical/horizontal)
Response time	6(GTG) ms
Life Time	30,000 hours
VESA	400×400mm

Signals

Input	DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

General

Consumption (Standard)	<170W
Consumption (Standby)	≤0.5W

Features:

- 4K Ultra-HD resolution
- Industrial level LCD panel, suitable for continuous 24/7 operation
- Slim 8mm narrow bezel design
- High fidelity digital processing for a brilliant and vivid video
- Built-in 3D COMB filter and 3D Noise Reduction
- 6ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- 178°/178° wide uninterrupted viewing angle
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Wide array of connectivity options HDMI, DP, VGA, USB, Audio, RS232



Power Supply	AC100~240V (+/-10%), 50/60 Hz
Net Weight	25.2kg
Gross Weight	35kg
Dimensions(no base)	1227.2×699.6×65.0mm
Package(W×H×D)	1410×875×255mm
Work Environment	Temperature: 0℃~40℃
	Humidity: 10%~85%

Accessory

Standard	HDMI cable, power cable, hanging bracket
Optional	Pedestal

Dimensions(mm)

