

iDS-7200HQHI-K1/S SERIES TURBO ACUSENSE DVR



Features and Functions

VCA Detection

- Deep learning-based analysis: re-recognition of the human body or vehicle target in behavior detection to filter false alarm, supports 2-ch detection for iDS-7204HQHI-K1/2S and 4-ch for iDS-7208HQHI-K1/4S

Video Input and Transmission

- Self-adaptive HDTVl/HDCVl/AHD/CVBS signal input
- When enhanced IP mode enabled, up to 6-ch 6 MP IP cameras input for iDS-7204HQHI-K1/2S; 12-ch 6 MP IP cameras input for iDS-7208HQHI-K1/4S and 24-ch 6 MP IP cameras input for iDS-7216HQHI-K1/4S
- Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTVl signal

Compression and Recording

- H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras
- Connectable to H.265+/H.265/H.264+/H.264 IP cameras
- H.265 Pro+/H.265 Pro can be enabled to improve encoding efficiency and reduce data storage costs
- Full channel recording at up to 4 MP lite resolution
- Supports real-time 1080p lite and when enabled, the image effect is similar with 1080p

Video Output

- Simultaneous HDMI/VGA output
- Separate CVBS output

Storage and Playback

- 1 SATA interface (up to 10 TB capacity per HDD)
- 4/8/16-ch synchronous playback
- Smart search for efficient playback
- Supports the 3rd party cloud storage (Dropbox/Google Drive/Microsoft OneDrive)

Smart Function

- Supports multiple VCA (Video Content Analytics) events for both analog and smart IP cameras
- iDS-7216HQHI-K1/4S supports 1-ch sudden scene change detection

Network & Ethernet Access


- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- 1 RJ45 10M/100M Ethernet network interface for iDS-7204HQHI-K1/2S and iDS-7208HQHI-K1/4S, and 1 RJ45 10M/100M/1000M Ethernet network interface for iDS-7216HQHI-K1/4S
- Output bandwidth limit configurable, up to 72M for iDS-7204HQHI-K1/2S; 96M for iDS-7208HQHI-K1/4S and 128M for iDS-7216HQHI-K1/4S



Specifications

Model		iDS-7204HQHI-K1/2S	iDS-7208HQHI-K1/4S	iDS-7216HQHI-K1/4S	
Video/Audio input	Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264			
	Analog video input	4-ch	8-ch	16-ch	
	HDTVI input	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 Note: The 3 MP signal input is only available for channel 1 of iDS-7204HQHI-K1/2S, for channel 1/2 of iDS-7208HQHI-K1/4S, and for channel 1/2/3/4 of iDS-7216HQHI-K1/4S.			
	AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30			
	HDCVI input	1080p25, 1080p30, 720p25, 720p30			
	CVBS input	PAL/NTSC			
	IP video input		Up to 6-ch	Up to 12-ch	Up to 24-ch
			Up to 6 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras		
	Audio compression	G.711u			
	Audio input	1-ch, RCA (2.0 Vp-p, 1 K Ω)			
Video/Audio output	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 \times 576, NTSC: 704 \times 480			
	HDMI/VGA output	1-ch, HDMI, 1-ch, VGA, 1920 \times 1080/60Hz, 1280 \times 1024/60Hz, 1280 \times 720/60Hz, 1024 \times 768/60Hz, HDMI/VGA Simultaneous Output			
	Encoding resolution@ Frame rate	Main stream: When 1080p Lite mode not enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)			
		Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)			
	Video bit rate	32 Kbps to 6 Mbps			
	Audio output	1-ch, RCA (Linear, 1 K Ω)			
	Audio bit rate	64 Kbps			
	Dual stream	Support			
	Stream type	Video, Video & Audio			
	Synchronous playback		4-ch	8-ch	16-ch
Network management	Remote connections	32	64	128	
	Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF			
Hard disk	SATA	1 SATA interface			
	Capacity	Up to 10 TB capacity for each disk			
External interface	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 K Ω) (using the 1 st audio input)			
	Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface		
	USB interface	2 \times USB 2.0			
	Serial interface	RS-485 (half-duplex)			
General	Power supply	12 VDC			
	Consumption (without HDD)	\leq 10 W	\leq 18 W	\leq 25 W	
	Working temperature	-10 $^{\circ}$ C to +55 $^{\circ}$ C (+14 $^{\circ}$ F to +131 $^{\circ}$ F)			
	Working humidity	10% to 90%			
	Dimensions (W \times D \times H)	315 \times 242 \times 45 mm (12.4 \times 9.5 \times 1.8 inch)			
Weight (without HDD)	\leq 1.16 kg (2.6 lb)	\leq 1.78 kg (3.9 lb)	\leq 2 kg (4.4 lb)		

Physical Interfaces



NOTE The rear panel of iDS-7204HQHI-K1/2S provides 4 video input interfaces. The rear panel of iDS-7208HQHI-K1/4S provides 8 video input interfaces.

Index	Description	Index	Description
1	VIDEO IN	7	LAN Network Interface
2	AUDIO IN, RCA Connector	8	RS-485 Serial Interface
3	AUDIO OUT, RCA Connector	9	12 VDC Power Input
4	VGA Interface	10	Power Switch
5	HDMI Interface	11	GND
6	USB Interface	12	VIDEO OUT

Available Models

iDS-7204HQHI-K1/2S, iDS-7208HQHI-K1/4S, iDS-7216HQHI-K1/4S

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com