



- 2.0 Mp resolution
- IP66 rating
- IR leds
- PoE support
- 3-Axis mounting
- ONVIF 2.4 protocol support

IP Camera		
Model	IPD-2SP-IR	
Version	2.3	
Image Sensor		
Sensor	1/2.8" FullHD Sony Ultra	
Pixel Size, μm	2.8x2.8	
Resolution, points@fps	Main stream	PAL:1920x1080@25, 1280x720@25, 704x576@25, NTSC:1920x1080@30, 1280x720@30, 704x576@30
	Sub stream	PAL:704x576@25, 320x288@25, NTSC:704x576@30, 320x288@30
Day/Night mode	Auto/Color/Black&White	
Sensitivity, Lux/Iris	Color 0.01Lux@F1.2, Black/White: 0.001 Lux@F1.2	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AES, AGC, AWB, BLC, OSD, PrivacyMasks	
Codec profile	H.264/MJPEG/H.265	Baseline / Main / High
	Auto	1/50-1/10000
Exposure mode, s	Manual	0.256-65.536
	Constant	1024-8192
Bitrate Type, kb/s	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm	2.8	
Iris, F	1.4	
Angle of View, °	Horizontal	91
	Vertical	75
lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control	-	
IR LED		
Distance, m	Up to 25	
Number of LEDs, pcs.	24	
Beam Spread, °	60	
Wavelength, nm	850	
IR Cut Filter	Auto	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Network functions	DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP	
Languages supported	English	
Default IP address	http://192.168.1.88	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	2000	
RTSP port	554	
RTSP string	Main stream	rtsp://ip/av0_0&user=admin&password=admin
	Sub stream	rtsp://ip/av0_1&user=admin&password=admin
Control port	5000	
Configuration software	-	
Monitoring program	Partizan CMS	
Mobile software(support)	-	
Protocol integration	ONVIF 2.4+	
Dimensions		
Size, mm	Total length	86
	Housing	Ø110x86
	Bracket	-
Weight, g	375	
Common		
Power Supply	DC12V, A	0.5
	PoE, Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Inputs	-
	Outputs	-
Memory card	-	
Housing material	Металл	
Bracket material	-	
IP rating	66	
IK rating	-	
Operating temperature, °C	-40 - +60	
Warranty, years	3	