

AE-DC5313-C6 Pro

Dashcam



- High Resolution Up to True 1600p (2560 x 1600)
- Wide Field of View Angle up to 130° Diagonal, 106° Horizontal
- f/1.6 Large Aperture for Crisp Night Imaging
- 4" Non-Touch Screen
- Microphone and Speaker
- GPS
- Wi-Fi AP Module
- G-Sensor Module Supports Collision Detection and Incident Footage Protection
- MicroSD Card Up to 128 GB Supported
- Phone App for Setup, Live View, Recording, Search and Backup, etc.
- Voice Control and ADAS (Advanced Driver Assistant System)

The Hikvision AE-DC5313-C6 Pro HD Dashboard Camera is a high resolution automotive dash cam that features easy installation and operation. The device communicates with its phone app through built-in Wi-Fi.

The built-in G-Sensor automatically locks the currently recording video when it senses a crash or strong vibration, to prevent it from being overwritten. MicroSD cards up to 128 GB are supported.

The built-in mic and speaker records and plays back audio.

Available Model

AE-DC5313-C6 Pro









Specifications

| | AE-DC5313-C6 Pro |
|-------------------------|--|
| _ | AE-DC3313-C0 PTO |
| Camera | |
| Image Sensor | CMOS |
| Resolution | 1600p @ 30 fps, 1440p @ 30 fps, 1080p @ 30 fps |
| Angle Adjustment | Diagonal: 130°, horizontal: 109° |
| Aperture | <i>f</i> /1.6 |
| Built in Display Screen | 4" non-touch screen with 640 x 480 resolution |
| Video Compression | Н.265 |
| OSD | Display time, date, etc. |
| Image Format | JPEG |
| Storage | MicroSD card, maximum 128 GB |
| Communication Module | Wi-Fi AP |
| Sensor | G-sensor, GPS |
| Interfaces | |
| Power Supply | USB 2.0 |
| Audio Input | Built-in microphone |
| Audio Output | Built-in speaker |
| General | |
| Working Temperature | -20° to 70° C (-4° to 158° F) |
| Working Humidity | 95% non-condensing |
| Power Supply | 5 VDC, 1 A |
| Power Consumption | Maximum 3 W |
| Dimension (L x W x H) | |
| (without bracket) | (III PEC.1 X III C 1) III II C) III C 1 |
| Weight | 123 g (4.34 oz) |
| | |

Dimensions (unit: mm)



