

DHI-ISC-ETA1-R003C-B

AM Label R003C-B Black



System Overview

The AM Label can be used together with the Acousto-Magnetic antenna to effectively prevent the theft from the goods.

Features

Suitable for Abundant Products

Apply to any flat non-metallic surface, easy to use.

Extremely Low Cost

Disposable products, needs to be demagnetized after it's sold.

Good Detection Effect

High detection rate, good anti-theft effect.

Scene

The label can be fixed on various goods.

Technical Specification

Performance

Technology	Acousto-Magnetic (AM)
Detection Frequency	58 kHz \pm 0.5 kHz
Antenna Detection Distance	\leq 0.8 m (Based on system performance)
Shell Material	Polyethylene Terephthalate (PET)
Marking	Blank
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

General

Color	Black
Length	40 mm (1.57") \pm 0.5 mm (0.02")

- Easy to use, suitable for most commodities.
- Small in size, able to provide concealed protection.
- Adopts self-adhesive process, which has good adhesion and less residual adhesive.

Width	10 mm (0.39") \pm 0.5 mm (0.02")
Thickness	1.44 mm (0.06") \pm 0.2 mm (0.01")
Packaging	20,000 pcs per carton
Carton Dimension	420 mm \times 290 mm \times 230 mm (16.54" \times 11.42" \times 9.06")
Carton Weight	11 kg (24.25 lb)
Minimum Order Quantity	1 carton

Environmental Constraints

Temperature	10 °C to 40 °C (50 °F to 104 °F)
Humidity	10 %–90 % (RH)

Ordering Information

Type	Model	Description
AM Label	DHI-ISC-ETA1-R003C-B	AM Label Blank R003C-B Black 20000 pcs