


# DHI-ISC-ETR1-1965-T

Transparent RF Label 1965-T



## System Overview

The RF Label can be used together with the Radio-Frequency antenna to effectively prevent the theft from the goods.

## Features

### Suitable for Various Goods

Apply to any flat non-metallic surface, easy to use.

### Extremely Low Cost

Disposable products, needs to be demagnetized after it's sold.

### Good Detection Effect

High detection rate, good anti-theft effect.

## Scene

The label can be fixed on various goods.

## Technical Specification

### Performance

Technology	Radio-Frequency (RF)
Detection Frequency	8.2 MHz $\pm$ 0.4 MHz
Antenna Detection Distance	$\leq$ 0.8 m (Based on system performance)
Shell Material	Copper Plate Paper
Marking	Blank
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

### General

Color	Transparent
Length	65 mm (2.56") $\pm$ 0.5 mm (0.02")

- Easy to use, suitable for most commodities.
- Adopts transparent design, able to provide concealed protection.
- Adopts self-adhesive process, which has good adhesion and less residual adhesive.

Width	19 mm (0.75") $\pm$ 0.5 mm (0.02")
Thickness	0.2 mm (0.0079") $\pm$ 0.02 mm (0.00079")
Packaging	20,000 pcs per carton
Carton Dimension	320 mm $\times$ 320 mm $\times$ 135 mm ( 12.60" $\times$ 12.60" $\times$ 5.31")
Carton Weight	7.50 kg (16.53 lb)
Minimum Order Quantity	1 carton

### Environmental Constraints

Temperature	10 °C to 40 °C (50 °F to 104 °F)
Humidity	10 %–90 % (RH)

## Ordering Information

Type	Model	Description
RF Label	DHI-ISC-ETR1-1965-T	Transparent RF Label 1965-T 20000 pcs