

# DHI-ISC-ETR3A-T606B-S

RF Mini Spider Net Super Lock 3A



### System Overview

Mini Spider Net is a high-performance alarming tag. It can accommodate goods of various sizes. The length of the wire rope can be adjusted by rotation to suit all kinds of packaging boxes. When the tag enters the protection mode, the wire rope will be locked, and cutting the net will trigger a huge alarm sound and LED flash. At the same time, it also has excellent detection rate with AM anti-theft antenna. Commonly used in a variety of retail stores.

# Features

# **Suitable for Abundant Products**

Strong fixation effect, can be effectively fixed on valuable goods, not easy to be damaged unless the special unlocking device is used.

#### **High Security Protection**

Breaking the tag will trigger a loud alarm tone, which can alert guards and effectively deter theft.

# **Good Detection Effect**

High detection rate, good anti-theft effect.

#### Various specifications

Multiple net sizes are available.

#### Multiple alarm modes

When the tag passes through the antenna, both the antenna and the tag will alarm. When the net is cut off, the tag will alarm.

# Scene

The tag can be fixed on small and medium-sized valuable goods.

- $\cdot$  Built in alarm function, triggered when tag or net damaged.
- $\cdot$  High detection rate, excellent anti-theft effect.
- $\cdot$  Wire rope mesh bag provides all-round protection for commodities.
- · Powerful locking mechanism, effectively preventing man-made damage.
- $\cdot$  Environmentally friendly and economical, can be reused after unlocking.
- $\cdot$  Small and light design, high detection performance.
- · Support three alarm modes.

# **Technical Specification**

| Performance Parameters           |  |  |  |
|----------------------------------|--|--|--|
| Technology                       | Radio-Frequency (RF)   |  |  |
| Detection<br>Frequency           | 8.2MHz±0.25MHz   |  |  |
| Antenna<br>Detection<br>Distance | $\leq$ 0.8 m (Based on system performance)   |  |  |
| Shell Material                   | Acrylonitrile Butadiene Styrene (ABS)  |  |  |
| Lock Strength                    | Super  |  |  |
| Certifications                   | Conform with RoHS<br>Directive 2011/65/EU, 2015/863/EU and REACH regulations as<br>defined in EC No 1907/2006 and subsequent amendments. |  |  |
| General Parameters               |  |  |  |
| Alarm Sound<br>Pressure          | ≥ 90 dB  |  |  |
| Alarm Duration                   | 5 min ± 10 s   |  |  |
| Low Battery<br>Alert             | Yes (When Enter Protection Mode)   |  |  |
| Battery Model                    | CR2032   |  |  |
| Battery Life                     | ≥ 2 years  |  |  |
| Flashing Interval                | 12 s ± 2 s   |  |  |
| Tensile Capacity                 | ≥ 350 N  |  |  |
| Net Bag Length                   | 360mm (14.7")  |  |  |
| Color                            | Black  |  |  |
| Length                           | 50.4 mm (1.98") ± 0.5 mm (0.02")   |  |  |
| Width                            | 50.4 mm (1.98") ± 0.5mm (0.02")  |  |  |
| Thickness                        | 34.8 mm (1.37") ± 0.5 mm (0.02")   |  |  |
| Weight                           | 94g(0.21lb)  |  |  |
| Packaging                        | 100 Tags per Carton  |  |  |
| Carton<br>Dimension              | 470 mm × 250 mm × 330 mm (18.5'' × 9.84'' × 12.99'')   |  |  |

# ISC-ETX5 Series | DHI-ISC-ETR3A-T606B-S

| Carton Weight             | 10 kg (22.05 lb) |  |  |  |
|---------------------------|------------------|--|--|--|
| Environmental Constraints |                  |  |  |  |
| Temperature               | 0 °C - 45 °C     |  |  |  |
| Humidity                  | 20 % – 90 % (RH) |  |  |  |
|                           |                  |  |  |  |

| Ordering Information |                       |   |  |
|----------------------|-----------------------|---|--|
| Туре                 | Model                 | Description                                       |  |
| Alarming Tag         | DHI-ISC-ETR3A-T606B-S | RF Mini Spider Net 3A Alarming<br>Tag 36cm 100Pcs |  |

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.