

# DHI-ISC-ETR5-T041

RF Pencil Tag T041



The RF Pencil Tag can be used together with the Radio-Frequency antenna to effectively prevent the theft from the goods.

F	ea	tu	ire	S

### **Suitable for Textile Products**

Strong fixation effect, can be effectively fixed on clothes and other items, not easy to be damaged unless the special unlocking device is used.

### **High Reuse Rate**

High reuse rate after recycling.

## **Good Detection Effect**

High detection rate, good anti-theft effect.

Length

The tag can be fixed on various goods, such as clothing, shoes and hats, etc.

Technical Specification			
Performance			
Technology	Radio-Frequency (RF)		
Detection Frequency	8.2 MHz ± 0.4 MHz		
AM Antenna Detection Distance	≤ 0.8 m (Based on system performance)		
Shell Material	High Impact Polystyrene		
Lock Strength	Standard		
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.		
General			
Color	Grey		

<ul> <li>Environmentally friendly and economical, can be reused after unl</li> </ul>	locking.
--	----------

- · Small and light design, high detection performance.
- · High detection rate, excellent anti-theft effect.
- Lower labor operating costs, widely applicable in merchandising shops.
- Powerful locking mechanism, effectively preventing man-made damage.

Width	13 mm (0.51") ± 0.5 mm (0.02")		
Label Thickness	18.5 mm (0.73") ± 0.5 mm (0.02")		
Packaging	1000 RF Tags per carton		
Carton Dimension	400 mm × 300 mm × 160 mm ( 15.75" × 11.81" × 6.30")		
Carton Weight	7.0 kg (15.4 lb)		
Minimum Order Quantity	1000 pcs		

# **Environmental Constraints**

Temperature	Maximum storage temperature not to exceed 60 °C for 96 hours at 80% RH.
Humidity	Maximum storage humidity not to exceed 80% RH for 96 hours at 60 °C.

Ordering Information				
Туре	Model	Description		
RF Tag	DHI-ISC-ETR5-T041	RF Pencil Tag T041		

 $\ \ \, \mathbb{O}$  2021 Dahua. All rights reserved. Design and specifications are subject to change without notice Pictures in the document are for reference only, and the actual product shall prevail. Rev 001.001

53 mm (2.09") ± 0.5 mm (0.02")