

DHI-ISC-ETRS-0004

EAS RF Sample Package



- Includes various types of EAS tag samples.
- Suitable for the installation of all kinds of goods to meet the needs of product protection.

System Overview

EAS RF Sample Package contains up to 8 kinds of RF band EAS tags for functional and performance testing. Each kind of hard tag 5 pcs. The tags can be fixed on the goods in various forms to achieve the purpose of protection with EAS anti-theft antenna.

Features

EAS Tags Introduction

EAS tag is an kind of anti-theft device containing a specific frequency sensing element. It is installed on the product to be protected and used with anti-theft antenna.

Application Scenarios

Suitable for the display and protection of clothing, daily necessities, tools, 3C electronics and other products.

Scene

Customers interested in purchasing the EAS RF tags.

Technical Specification

Performance Parameters

Technology	Radio-Frequency (RF)
Detection Frequency	8.2 MHz \pm 0.4 MHz
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

Sample Information

Name	Model	Quantity
RF Plastic Belt Bottle Tag B038	DHI-ISC-ETRS-B038	5
RF Optical Tag T100	DHI-ISC-ETRS-T100	5
RF Pencil Tag T010	DHI-ISC-ETRS-T010	5
RF Pencil Tag T041	DHI-ISC-ETRS-T041	5

RF Lanyard Tag T040	DHI-ISC-ETRS-T040	5
RF Square Tag T001	DHI-ISC-ETRS-T001	5
RF Round Tag T013	DHI-ISC-ETRS-T013	5
RF Ink Tag T171	DHI-ISC-ETRS-T171	5

General parameters

Length	260 mm (10.24") \pm 0.5 mm (0.02")
Width	180 mm (7.09") \pm 0.5 mm (0.02")
Thickness	50 mm (1.97") \pm 0.5 mm (0.02")
Weight	0.44 kg (0.97 lb)
Minimum Order Quantity	1 box

Environmental Constraints

Temperature	0 °C to 45 °C (32 °F to +113 °F)
Humidity	20 % -90 % (RH)

Ordering Information

Type	Model	Description
Sample Package	DHI-ISC-ETRS-0004	EAS RF Sample Package