

KIT PRODUCT TECHNICAL DATASHEET

KIT B70/2ML/20

New 

Brushless 

Intensive use 

IPU technology 



Composition KIT B70/2ML/20

CODE	DESCRIPTION	QTY
B70/2ML/BOX	Digital control 24V for 2 BRUSHLESS motor, with plastic box.	1
H93/RX22A/I	Plug-in receiver fixe code 2 channels 433,92 Mhz (500 storable codes) for control unit series H70, B70, EDGE, CTRL and F70.	1
SYNUS/2	Dual code transmitter (modality fixed code or rolling code), 433,92 Mhz. 2 channels, with radio for copy.	2
R90/F4ES	Pair of external photocells synchronized 24V AC/DC (max. 4 pairs).	1
FIFTHY/24	LED flashing light series FIFTHY 24V with integrated antenna.	1
R99/C/001	Signboard "Automatic Opening".	1

PRODUCT TECHNICAL SPECIFICATIONS

Power line supply	230V AC - 50 Hz
Operating temperature	-10+55 C°
Protection level	IP54
N. motors activated	2 Brushless motor
Max power per motor	110W
Max courtesy light charge	100W 230V AC - 40W 24V AC/DC
Max power gate open light	3W (24V DC)
Max voltage accessories output	10W (24V DC)
Electrical-Lock max power	15W (12V DC)
Flash light voltage	24V DC
Max flashing light charge	25W
Battery	Optional

Maximum dimension product in mm (L x W x H)	330 x 230 x 115
Product weight packed (Kg)	5,3
Number items per pallet/box	49

PRODUCT ACCESSORIES




B71/BC/INT

Kit for emergency batteries charger for Brushless digital controller 24V DC with plug-in cord, with 2 recovery batteries 12V DC, 1,2 Ah. Box case included.



B71/BC/EXT

Kit for emergency batteries charger for Brushless digital controller 24V DC with plug-in card, with 2 recovery batteries 12V DC, 4,5 Ah. Box case included.



B71/BC/BOX

Kit for emergency batteries charger for Brushless digital controller 24V DC. Box case included and without recovery batteries.



B71/PBX24/BOX

Hybrid inverter, "Network Assisted" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels or mains supply for powering the 24V DC brushless digital controllers with a mains voltage of 230V AC.



B71/PBX24/BOX/115

Hybrid inverter, "Network Assisted" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels or mains supply for powering the 24V DC brushless digital controllers with a mains voltage of 115V AC.



B71/PBX/BOX

Hybrid inverter, "Full Solar" version, for powering the automation. Also provides a battery-charger function thanks to the connection to the solar panels for powering the brushless digital controllers.



B74/BCONNECT

Module Wi-Fi B-CONNECT - Remote management and programming system in IP and CLOUD web browser mode via Wi-Fi hot spot P2P connection for Brushless control units (B70/2ML - EDGE1 - CTRL - CTRL/P - B70/1DC - B70/1DCHP - B70/1T - B70/1THP - F70/IPU36).