

DHI-LM50-F400

50" UHD LED Monitor



Features:

- · 4K Ultra-HD resolution
- · Suitable for continuous 24/7 operation
- · 8ms response time for no motion blur, judder or ghosting
- · 1.07G colors for realistic and immersive visual experience
- · High fidelity digital processing for a brilliant and vivid video
- \cdot 178°/178° extra-wide viewing angle for overall viewing performance
- · Professional thermal design to extend equipment lifespan













Technical Specification

Model	DHI-LM50-F400
Display	
Screen Size	50"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness	300cd/m²
Contrast Ratio	5000:1
Display Color	1.07G (8 Bits+FRC)
Viewing Angle	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz
Signals	
Input	HDMI 2.0×1, HDMI1.4×1, USB 2.0×1, VGA×1, Audio in×1, RS232×1
Output	Speaker×2 (7W)
General	
Power Supply	AC100-240V, 2.5A, 50/60 Hz

Consumption (Standard)	110W	
Consumption (Standby)	≤0.5W	
Net Weight	10.4Kg	
Gross Weight	13.8Kg	
Bezel Width	8.24mm (U/L/R), 22.62mm (B)	
VESA	200×200mm	
Dimension without base (W×H×D)	1113.04×649×87.2mm (43.8"×25.6"×3.4")	
Package(W×H×D)	1240×800×160mm (48.8"×31.5"×6.3")	
Work Environment	Temperature	0°C~40°C
	Humidity	10%~80%
Work Environment	·	

Accessory

Standard	Power cable, remote control, pedestal
Optional	Hanging bracket

Certifications

Certifications CE/FCC



Dimensions(mm)











