



JA-154A Wireless battery indoor siren

The wireless siren can be easily mounted anywhere within range of the system radio. Flexible installation is made possible by power from 3 AA batteries.

○ [Declaration of conformity - JA-154A \(PDF 540.8 kB\)](#)


Technical specifications

Power	3x Alkaline battery, type LR6 (AA) 1.5 V/2.45 Ah Batteries are not included in the packaging.
Typical lifetime of batteries	approx. 2 years
LowBatt state	<3,3 V
Quiescent current consumption	135 μ A
Maximum current consumption	250 mA
Current consumption during acoustic indication	250 mA
Communication frequency	868.1 MHz, JABLOTRON protocol
Maximum radio-frequency power (ERP)	<25 mW
Maximal acoustic output	85-88 dB
Type of warning device	type W
Dimensions	100 x 67 x 40 mm
Weight (without batteries)	97 g
Classification	Security grade 2/Environmental class II (EN 50131-1)
Environment	Indoor general
Operating temperature range	-10 °C do +40 °C
Average operating humidity	75% RH, without condensation
Certification body	Trezor Test (no. 3025)

In compliance with

EN IEC 63000, EN 50130-4, EN 55032, EN IEC 62368-1, ETSI EN 300 220-1, -2, EN 50131-1, EN 50131-5-3, EN 50131-4, EN 50131-6

Recommended screw

3 x  \varnothing 3,5 x 40 mm (flat head)